

# VIASENSOR

N<sub>2</sub>O, 0-1,000PPM GAS ANALYZER  
G200

DENTAL STAFF SAFETY  
MEDICAL STAFF SAFETY



G200

The **G200 N<sub>2</sub>O analyzer**  
is designed to **safety check** background  
and **breathing zone levels of N<sub>2</sub>O**  
(0–1,000ppm)

- ✚ Ideal for Dental Industry Applications
- ✚ Portable Analyzer for breathing zones
- ✚ Easy to read display

# VIASENSOR

# VIASENSOR

N<sub>2</sub>O, 0-1,000PPM GAS ANALYZER  
G200



MEDICAL STAFF SAFETY

## Features

- 0 – 1,000 ppm N<sub>2</sub>O
- Storage for 1000 readings
- TWA calculated
- Leak detection
- User settable alarms
- Data download for graphing and reporting

## Applications

- Operating Rooms
- Dental Practices
- Veterinary clinics
- X-ray departments

## Key Benefits

- Accurate verification of exposure limits
- Dual purpose background analyzer or personal analyzer
- Leak detection for N<sub>2</sub>O storage
- Highly portable

### TECHNICAL SPECIFICATIONS:

#### Gas Ranges

Gas Measured	N <sub>2</sub> O	By custom dual wavelength infra-red sensor with reference channel
Range	N <sub>2</sub> O	0-1,000ppm 0-10,000ppm (leak detection mode, indication only)
Measurement Accuracy*	N <sub>2</sub> O	<b>Resolution:</b> 1ppm +/-5 ppm for 0-100 ppm after calibration ± 1.5% of range for 101ppm and above, after calibration
Response time, T <sup>90</sup>	N <sub>2</sub> O	<40 seconds

\* plus accuracy of calibration gas used

#### Facilities

Visual and audible alarm	User selectable N <sub>2</sub> O and TWA alarms
Communications	USB type B mini-connector, HID device class
Data Storage	1,000 reading sets + 270 events 50 Site ID's and 300 sample point ID's

#### Pump

Flow	100cc/min typically
------	---------------------

#### Environmental Conditions

Operating temperature	32F–122F (0°C – 50°C)
Relative humidity	5% to 95% non condensing
Barometric pressure	500 to 1,500mb
IP rating	IP40

#### Power Supply

Battery type	Li Ion
Battery life	10 Hours (8 hours with pump)
Battery charger	5v DC external power supply and internal charging circuit
Charge time	3 Hours
Alternative power	USB connector DC power supply

#### Physical

Weight	1.1 lbs (500 grams)
Size	L 6.5 in, W 3.9 in, D 2.2 in (L 165mm, W100mm, D55mm)
Case Material	ABS / Polypropylene with Silicone Rubber Inserts
Keys	17 Resin capped Silicone rubber keys
Display	Liquid crystal display, 128 x 64 pixel With RGB LED back-light
Gas sample filters	User replaceable PTFE water trap filter and - Soda lime CO <sub>2</sub> filter



深圳为尔康科技有限公司 联系人：曾祥满 手机：13632925349

QQ：274798107 电话：0755-28896837 地址：深圳市龙岗区沙平北路111号6008

网址：www.medicalQC.com 邮箱：szchina1718@163.com