

## **UMS Scanning System**



UMS is a fully automated scanning system that has been specifically designed to automate the repetitive tasks of acquisition, display, storage and processing of data associated with the measurement and mapping of acoustic fields.

Ultrasound measurements rely on the ability to accurately measure the acoustic field. To facilitate this, UMS incorporates the ability to conduct:

- computer controlled movement of XYZ axes and data acquisition
- automatic alignment on the acoustic axis of the transducer
- beam profiling and planar scanning with real-time display
- focal region localisation and characterisation
- correction for hydrophone frequency response and calculation of pressure waveforms
- calculation of derived intensity, power and index parameters for regulatory reporting
- preparation and running user-defined measurement sequences (scripts)
- direct-to-PDF report generation



深圳为尔康科技有限公司 曾生:13632925349 QQ:274798107

地址:深圳市龙岗区沙平北路111号吉茂大厦608A

网址:www.medicalqc.com

## TYPICAL SYSTEM SPECIFICATION

Water tank dimensions	1 m (L) x 0.5 m (W) x 0.6 m (H) <sup>*</sup>			
Linear motion range	0.75 m x 0.5 m x 0.5 m <sup>+</sup>			
Ideal frequency range	0.5 MHz <sup>‡</sup> - 60 MHz			
Number of motorised axes	3 Linear axes, XYZ			
	(expandable up to 8 axes including up to 2 rotational axes if			
	required)			
Positional error / Linear repeatability	+/- 6 μm (via load-mounted encoders)			
Linear resolution	1 μm			
Angular resolution	0.01°			
Measurement orientation	Horizontal or vertical/top-down (user configurable)			
Working speed	20 mm/s			
Working load	Up to 15 kg			
Included hardware	L-shaped hydrophone mount & multipurpose transducer mount			
Data acquisition	Via modern digital oscilloscope (can be supplied if needed)			
System software	PC supplied with preloaded applications for acquisition and post			
	processing of data			

AUTOMATIC CALCULATION OF

Peak positive and negative pressures	ITA, ITP, IPA and peak/averages e.g. ISPTA			Pulse duration
Beam width, area and focal length	Power	MI	f <sub>awf</sub>	Frequency spectrum



Figure 1 - UMS acquisition interface

Figure 2 - UMS post-processing interface

All information is based on results gained from experience and tests, and is believed to be accurate but is given without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside the control of Precision Acoustics Ltd.



**深圳为尔康科技有限公司** 曾生:13632925349 QQ:274798107 电话:0755-28896837 地址:深圳市龙岗区沙平北路111号吉茂大厦608A 网址:www.medicalqc.com